# Aventho wireless







- Dynamic Tesla high-end drivers
- Bluetooth® wireless technology for more freedom of movement
- Operation via touch pad
- Operating range up to 10 m
- Battery runtime > 30 hours
- Audio Codecs: Qualcomm® aptX™ and aptX™ HD, Advanced Audio Coding (AAC), Low Complexity Subband Codec (SBC)
- LED to display the operating status
- Voice prompted battery status

### **DESCRIPTION**

The Aventho wireless is a headphone with Bluetooth® wireless technology featuring an extremely homogeneous, balanced sound. With a range of up to 10 metres, the headphones allow for freedom of movement, while being compatible with all devices such as smartphones, tablets and computers with Bluetooth®. The Tesla drivers feature a crystal-clear sound.

The headphones are switched on or off via a button. An LED displays the operating status. A microphone is integrated in the left ear cup. A touch pad on the right ear cup is used to control the media playback and calls. With the beyerdynamic MIY App users can personalise the sound of their Aventho wireless. At the same time, the app provides information about the listening habits of the user so that the hearing can be protected. The app is available for Apple iOS and Android and can be downloaded from the Apple App Store and Google Play Store.

Voice prompts on the battery status also contribute to the ease of operation. The integrated battery itself is charged via the USB port on

The delivery includes an audio cable with mini jack plug (3.5 mm) so that the headphones can also be used as a normal headphone if a Bluetooth® device is not available or if the battery is empty. When not in use, the Aventho wireless can be stored in the included soft bag.



#### TECHNICAL SPECIFICATIONS

Transducer type dynamic	
Operating principle closed	
Frequency response 10 – 40,000 H	Z

Nominal impedance . . . . . . . . . . . 32  $\Omega$ 

Nominal SPL

with jack plug cable ..... 105 dB SPL (1 mW / 500 Hz)

Nominal power handling capacity . . 100 mW 

Sound coupling to the ear . . . . . . on-ear

Cable length and connector . . . . . 1.2 m, detachable,

3-pole mini stereo jack

(3.5 mm)

Bluetooth® . . . . . . . . . . . . . . . . 4.2 version

Frequency range. . . . . . . . . . 2.4000 – 2.4835 GHz

Power class . . . . . . . . . . . . 2.0

Supported profiles . . . . . . . . . . . . . HSP, HFP, A2DP, AVRCP, GAVDP Supported codecs . . . . . . . . . aptX<sup>™</sup>, aptX<sup>™</sup> HD, AAC, SBC

Operating range. . . . . . . . . up to 10 m

Charging time . . . . . . . . . . . 2 hrs. Battery capacity . . . . . . . . . . . . . . . 1050 mAh Charging port . . . . . . . . . . . USB-C Operating temperature. . . . . . . . 0 – 40 °C Weight without cable........... 238 g

## SUPPLIED ACCESSORIES

- Aventho wireless headphones
- Audio cable with mini jack plug (3.5 mm)
- Charging cable USB-A to USB-C
- Soft bag

#### Trademarks

The Bluetooth® wordmark and logos are registered trademarks of Bluetooth SIG, Inc. and all use of these trademarks by beyerdynamic is licensed. Other trademarks and trade names are the property of the respective owners.

Oualcomm aptX™ is a product of Oualcomm Technologies. Inc. and/or its subsidiaries. Qualcomm® is a registered trademark of Qualcomm Incorporated in the USA and in other countries. aptX™ is a registered trademark of Qualcomm Technologies International, Ltd.

1 of 1

beverdynamic GmbH & Co. KG Theresienstr. 8 | 74072 Heilbronn - Germany Tel. +49 (0) 71 31 / 617 - 300 | info@beyerdynamic.de | www.beyerdynamic.com

beyerdynamic